



MOISTURE-CURED, URETHANE ADHESIVE

Specifically Formulated for the Installation of Rubber Flooring

PRODUCT

INFORMATION

PRODUCT DESCRIPTION

US Rubber's SurvivorGrip is a solvent-free*, single component, trowel applied, moisture-cured urethane adhesive specifically formulated for the installation of rubber flooring. US Rubber's SurvivorGrip is a 0 VOC formulation as calculated by SCAQMD Rule 1168. Once cured, this adhesive is not adversely affected by exposure to moisture or water; its superior properties provide a tenacious bond to a variety of surfaces either indoors or outdoors. SurvivorGrip has been formulated to exhibit a unique combination of application properties including excellent trowelability, fast tack/grab, low odor and easy clean up.

SurvivorGrip may be used to adhere most rubber flooring, tile, stair treads, and nosing. SurvivorGrip may be used over all properly prepared substrates common to rubber flooring installations including; concrete, asphalt, plywood, cementitious-based patch / underlayments, terrazzo, and radiant heated flooring.

This product contains BLOCKADE® antimicrobial protection, which inhibits the growth of bacteria, mold, or mildew on the surface of the dried adhesive; the dried adhesive resists stains caused by mold.

DIRECTIONS FOR USE

Read and understand the data sheet completely before beginning installation. Follow the appropriate industry standards, including ASTM F710 Standard Practice for Preparing Concrete Floors to Receive Resilient Flooring. Various rubber flooring materials have vastly different substrate preparation and installation requirements; substrate preparation and installation requirements are key to a successful installation regardless of flooring material being installed. Always do a test area to ensure product satisfaction, including adhesion to substrate, and/or to become familiar with proper application techniques prior to use. Periodically lift away a section of the floor covering to assure that proper coverage is being attained.

SURFACE PREPARATION

Surfaces must be clean, dry and smooth; free of voids, projections, loose materials, oil, grease, sealers and all other surface contaminants. Mechanically remove all surface contaminants by scraping, sanding or scarifying the substrate. Surface areas

CHEMICAL & PHYSICAL PROPERTIES

Application Temperature	40°F - 100°F
Service Temperature	-40°F - 150°F
Flash Point	> 500°F
Viscosity	Creamy and Trowelable
Odor	Minimal
Color	Gray
Weight	13.75 lbs/gallon
Working Time at 72 F	30 - 40 minutes
Cure Time**	8 - 10 hours foot traffic; 24 hours for normal traffic
Freeze/Thaw	Stable
VOC Content	0 g/L as calculated by SCAQMD Rule 1168
Water Vapor Transmission Permeance	< 0.6 perms @ 60 mil
Tensile	185 psi
Shear-to-Concrete	200 psi
Elongation	>150%
Flammability (ASTM E-84)	Flame Spread Index = 25

**Cure time may vary depending on temperature and humidity.

requiring patching or leveling must be treated using Bostik® Ultra Finish, Webcrete 95TM& 98TM cement patches and/or Duralevel® 83PTM or Bostik SL-150 self-leveling underlayments (for interior use only). Refer to the use instructions of these products for proper installation. Durabond D-250TM Moisture Vapor Barrier Coating or D-261TM Extreme Moisture Vapor Barrier Coating are recommended for installations where excessive moisture and/or alkalinity issues may exist or might occur from the concrete slab. Please refer to the "Installation" section below for proper installation methods when using these moisture vapor barrier coatings.

INSTALLATION

Spread SurvivorGrip evenly with the proper trowel as described below. Open time is influenced by substrate porosity and atmospheric conditions (i.e. temperature, humidity, and air movement.) For best results maintain adhesive, floor covering, and room at a stable temperature of 50°F to 85°F for 24 hours before and after installation. Refer to the application instructions below for the recommended installation technique. Within 30-40 minutes, cut, fit and reposition the



floor covering as recommended. Roll the installation using the flooring manufacturer's recommendations. Periodically check back of floor covering to ensure 100% coverage of flooring materials backing.

Applications Over Durabond D-250 Moisture Vapor Barrier Coating: SurvivorGrip may be installed directly over D-250 without the requirement of a primer or cementitious layer. Refer to the technical data sheet for this product for proper application instructions.

Applications Over Durabond D-261 Extreme Moisture Vapor Barrier Coating: SurvivorGrip may be installed directly over D-261 without the requirement of a primer or cementitious layer. In lieu of using a single coat of D-261, two coats of D-250 may be used to mitigate the most extreme moisture conditions. Refer to the technical data sheets for these products for proper application instructions.

CURE TIME

Humidity affects cure to a greater degree than temperature; the higher the humidity, the faster the cure. Under normal conditions (70°F and 50% RH), light foot traffic is acceptable after 8 to 10 hours; normal traffic after 24 hours.

CLEANUP AND STORAGE

As you work, immediately clean any adhesive from rubber flooring with mineral spirits using a clean rag. Immediately clean all tools and equipment with mineral spirits before adhesive cures. Once cured this material can only be mechanically removed; which may damage some surfaces. The product should be stored in the original container in a cool, dry place.

LIMITATIONS

- Slab temperature should be between 40°F and 100°F during installation. Large fluctuations in temperature during installation and cure should be avoided.
- Do not use on wet, dusty, contaminated, or friable substrates; do not use over substrates/slabs treated with sealers or curing compounds; do not use in areas subject to hydrostatic head.
- Do not allow heavy traffic or rolling loads for a minimum of 24 hours.
- Prior to applying adhesive to rubber stair treads, lightly sand the entire back of the tread and nosing and wipe with denatured alcohol to remove any contaminants that may interfere with proper adhesion.

- Rubber flooring is available in a wide range of variations with a number of different backings; it is critical that a test is done prior to actual installation using the adhesive and flooring material to confirm compatibility, application techniques, and/or proper performance of the adhesive.
- Do not use SurvivorGrip over any gypsum-based materials.

PACKAGING

US Rubber's SurvivorGrip Urethane Adhesive is available in 4 gallon pails.

COVERAGE

Ensure proper adhesive transfer by using the recommended trowel sizes listed below.


STORAGE AND SHELF LIFE

Shelf life is one year from date of manufacturing in unopened, original packaging. Store at temperatures between 50°F and 100°F.


Re-Seal Partially Used Container: With pail upright, place a sheet of plastic (e.g. trash bag) over the top of the pail. Secure lid tightly over the plastic on top of pail. Carefully turn pail upside down. Plastic will help prevent the material from bonding the lid closed.

Re-Open Partially Used Container: Carefully turn pail right side up. Remove lid. Carefully cut and discard cured material and


**RECOMMENDED TROWELS FOR
MAXIMUM PERFORMANCE**



1/16" x 1/16" x 1/16"
Smooth backed products
Interior Applications Only
Coverage 95 ft² / Gallon



1/16" x 1/16" V-notch
Recycled rubber tile
or rolled goods.
Coverage 75 ft² / Gallon



1/8" x 1/8" x 1/8"
Rough backed products
All Exterior Applications
Coverage 80 ft² / Gallon

Trowel size is suggested to maximize coverage of adhesive. Periodically check coverage of adhesive during installation. Uneven sub flooring may require the use of either a leveling/patching material, or a larger notched trowel for proper coverage of adhesive. Always refer to the flooring manufacturer's recommended use instructions for proper trowel selection.

Colton, CA 92324 (888)
473-8453

www.usrubber.com

PLANT LOCATIONS
Colton, CA 92324

